

- [Strukton](#)

Strukton and subsidiaries

- [Strukton Go to strukton.com](#)
- [Strukton Civiel Go to struktonciviel.com](#)
- [Strukton International Go to struktoninternational.com](#)
- [Strukton Integrale ProjectenStrukton Integrale Projecten](#)
- [Strukton InternationalStrukton International](#)
- [Strukton Rail Go to struktonrail.com](#)
- [Strukton Worksphere Go to struktonworksphere.nl](#)



close menu menu



- [RSS](#)
- [Contact us](#)

Sealoflex® PMB for sealants

Cracks are a serious threat to pavement structures as they allow water to penetrate the base structure. It is therefore essential to treat cracks with appropriate fillers/sealants. Under the brand name Sealofill®, hot applied polymer modified bitumen is produced for crack filling and sealing asphalt and concrete pavements. The Sealofill® product has high elasticity, ductility and perfect bond within a wide temperature range. Sealofill® complies with the relevant ASTM standards for crack filler/sealants. Ooms supplies Sealofill® B.

Sealofill® B

- **Sealofill® B**
Sealofill® B is used to seal wide cracks, joints and routed cracks in asphalt and concrete pavements, with a minimum width of 15 mm. Sealofill® B is suitable for use in climates with both cold as well as hot temperatures

Delivery: fast and safe

Sealants can be supplied in boxes of 23 kg, in tankers and containers or directly from our bitumen plants.